



Royal Range Internal Stable Partitions Specification

(green text indicates upgrade from Prime Range)

Shiplap Cladding

Top grade redwood shiplap cladding 16mm x 150mm, fixed with 50mm sheradised ring shank nails.

Framework

The frameworks are manufactured with kiln dried timber, 47mm x 75mm. All timber is regularised and strength graded for structural use to C16-C24.

Kickboarding

All stables are kickboarded as standard to a height of 1.2m high with exterior grade 12mm Spruce plywood - multiple 5 layered for structural integrity.

Doors

Bottom doors only. Manufactured from 125mm x 25mm tongue, groove and v-jointed timber, ledged and braced.

Doors are lined with exterior grade plywood to give an overall thickness of 50mm.

Stable door size 1.1m x 1.3m high.

Doors are furnished with 1 x strong anti-chew strip, 1 x heavy duty kick-over latch, 1 x 225mm brenton bolt, 1 x 150mm cabin hook and 1 pair of heavy duty 600mm hook & band hinges. Top door frame protection is included.

Preservative

Sections are treated with an animal friendly preservative product to a golden brown finish before leaving our workshop.

Internal Partitions

Timber frame partitions with shiplap cladding to full height on all front walls. All stables are kickboarded internally to 1.2m high with very strong 12mm external grade plywood. Front walls include a large grill.

Other Details

All sections are 2.4m high when erected on one course of bricks.